

Powered height adjustable mount –
the StarBoard Integral

A complete mounting solution for the Hitachi projector and whiteboard

The new Integral StarBoard system enables the easy installation of Hitachi Interactive whiteboards (FX Series and DuoBoard) for use with ultra short throw Hitachi projectors.



Simple to use and quick to install

Made out of aluminum, this reliable powered support system is durable, strong yet light in weight. Installing the system could not be easier.

Ultimate flexibility

This system is designed to be used with the Hitachi FX series or the FX Duo, all sizes and all formats.

Flexible height and effortless to use

With an adjustable height of up to 85 cm, the system can be easily adjusted to the height of each user by simply pressing a button. The StarBoard integral is therefore instantly available for use by small children or adults alike.

A solution designed especially for the Hitachi interactive whiteboard board and the ultra short throw Hitachi projector.

Featuring unique Hitachi optical technology, the CP-A100/ED-A100/ED-A110 has an ultra short throw capability delivering a 60" projection at 42cm. This allows the projector to be sited very close to the screen eliminating shadowing effects. The StarBoard Integral is designed to maximize the advantages of this product.

There is no longer any need to spend hours to installing your projector!. This unique system will enable you to install and adjust the image for any size of interactive whiteboard in a matter of minutes.

Redefining the interactive whiteboard

HITACHI
Inspire the Next

Major advantages of 'StarBoard Integral'

- Durable, strong yet light in weight.
- Minimal time and money spent on installation.
- A very stable system, no new calibration is needed after adjusting the stand.
- Safe for use in the classroom or the boardroom.
- Flexibility: it can be used with all Hitachi FX Series and Fx DuoBoard interactive whiteboards.
- Easy to adjust the height.
- Elimination of shadow effects
- 3 side electrical outlets make it possible to the users to connect the projector, the computer and other peripherals.



Technical specifications

Stand

Model No.:	XAFXSTAND
Dimensions (mm):	2000 (H) x 800 (L) x 200 (W)
Weight (kg):	29
Packing dimensions (mm):	2100 (H) x 900 (L) x 300 (W)
Packing weight (kg):	30
Whiteboard product is compatible with:	FX 63, FX 77, FX DUO 50, FX DUO 63, FX DUO 77
Model which projector is compatible with:	Hitachi CP-A100/ED-A100/ED-A110
Material used:	Aluminium
Electrical outlets:	3 power outlets - Type F, CEE 7/4 (German "Schuko" 16 A/250 V earthed)
Adjustable height:	85 cm

Engine

Nominal torque:	20 N.m
Rated voltage:	230V, 50Hz
Protection class:	IP44

Remote Control

Control distance:	50 m
Rated voltage:	220V, 50Hz
Operating temperature:	-10°C to +70°C
Radio frequency:	433,92 MHz

Hitachi Software Engineering (UK) Limited
Interactive Media Solutions Division
Tel: +44 (0)207 246 6868
Fax: +44 (0)207 246 6860
Email: sales@hitachi-software.co.uk

Hitachi Software Engineering France S.A.S
Interactive Media Solutions Division
Tel: +33 (0)153 827 600
Fax: +33 (0)153 827 619
Email: starboard@hitachisoft-eu.com

Hitachi Software Engineering Europe AG
Interactive Media Solutions Division
Tel: +49 (0)30 8877 2600
Fax: +49 (0)30 8877 2610
Email: starboard@hitachisoft.de

Further information:

www.hitachisoft-eu.com

HITACHI
Inspire the Next